



Safety Data Sheet

DOW CHEMICAL COMPANY LIMITED
Safety Data Sheet according to Reg. (EC) N. 453/2010

Product Name: CARBOWAX™ PEG 200E

Revision Date: 15.04.2013

Print Date: 05 Jun 2014

DOW CHEMICAL COMPANY LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

Section 1. Identification of the substance/preparation and of the company/undertaking

1.1 Product identifiers

Product Name

CARBOWAX™ PEG 200E

Chemical Name: Polyethylene glycol 2

CAS-No. 25322-68-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

A partial list of examples include pharmaceutical products, personal care products, automotive products, household products, packaging products, petroleum chemicals, plastics, inks, coatings, adhesives, chemical intermediates, rubber processing, lubricants, metalworking fluids, mold release agents, ceramics, and wood treating.

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION

DOW CHEMICAL COMPANY LIMITED
DIAMOND HOUSE, LOTUS PARK,
KINGSBURY CRESCENT,
STAINES
England
TW18 3AG
UNITED KINGDOM

Customer Information Number:

0203 139 4000

SDSQuestion@dow.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact:

0031 115 694 982

Local Emergency Contact:

00 31 115 69 4982

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification - REGULATION (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

This product is not classified as dangerous according to EC criteria.

2.2 Label elements

Labelling - REGULATION (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria.

2.3 Other Hazards

No information available.

Section 3. Composition/information on ingredients

3.1 Substance

This product is a substance.

CAS-No. / EC-No. / Index	REACH No.	Amount	Component	Classification: REGULATION (EC) No 1272/2008
CAS-No. 25322-68-3 EC-No. Polymer	—	> 96.0 %	Polyethylene glycol 2##	Not classified
CAS-No. 111-46-6 EC-No. 203-872-2 Index 603-140-00-6	—	< 4.0 %	Diethylene glycol	Acute Tox., 4, H302 STOT RE, 2, H373
CAS-No. 107-21-1 EC-No. 203-473-3 Index 603-027-00-1	—	<= 1.0 %	Ethanediol; ethylene glycol	Acute Tox., 4, H302 STOT RE, 2, H373

CAS-No. / EC-No. / Index	Amount	Component	Classification: 67/548/EEC
CAS-No. 25322-68-3 EC-No. Polymer	> 96.0 %	Polyethylene glycol 2##	Not classified.
CAS-No. 111-46-6 EC-No. 203-872-2 Index 603-140-00-6	< 4.0 %	Diethylene glycol	Xn: R22
CAS-No. 107-21-1	<= 1.0 %	Ethanediol; ethylene glycol	Xn: R22

EC-No.
203-473-3
Index
603-027-00-1

Voluntarily disclosed component(s).

For the full text of the H-Statements mentioned in this Section, see Section 16.

See Section 16 for full text of R-phrases.

Section 4. First-aid measures

4.1 Description of first aid measures

General advice: If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin Contact: Wash skin with plenty of water.

Eye Contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

4.2 Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), no additional symptoms and effects are anticipated.

4.3 Indication of immediate medical attention and special treatment needed

Absorption may be promoted by damaged skin. J Pharm Sci. 1985 Oct;74(10):1062-6; Burns Incl Therm Inj 1982 Sep;9(1):49-52. Due to structural analogy and clinical data, this material may have a mechanism of intoxication similar to ethylene glycol. On that basis, treatment similar to ethylene glycol intoxication may be of benefit. In cases where several ounces (60 - 100 ml) have been ingested, consider the use of ethanol and hemodialysis in the treatment. Consult standard literature for details of treatment. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion. Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol®) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol (EG), di- or triethylene glycol (DEG, TEG), ethylene glycol butyl ether (EGBE), or methanol intoxication if available. Fomepizole protocol (Brent, J. et al., New England Journal of Medicine, Feb. 8, 2001, 344:6, p. 424-9): loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizole until serum methanol, EG, DEG, TEG or EGBE are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5. Fire Fighting Measures

5.1 Extinguishing Media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Extinguishing Media to Avoid: Do not use direct water stream. May spread fire.

5.2 Special hazards arising from the substance or mixture

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

5.3 Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

6.2 Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

6.3 Methods and materials for containment and cleaning up: Contain spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

Section 7. Handling and Storage

7.1 Precautions for safe handling

Handling

General Handling: See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Other Precautions: Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Store in original container. Use product promptly after opening. Avoid prolonged exposure to heat and air. Store in the following material(s): Stainless steel. Polypropylene. Polyethylene-lined container. Teflon. Glass-lined container. Plaste 3066 lined container. Plaste 3070 lined container. 316 stainless steel.

7.3 Specific end uses

See the technical data sheet on this product for further information.

Section 8. Exposure Controls / Personal Protection

8.1 Control parameters Exposure Limits

Component	List	Type	Value
Diethylene glycol	AIHA WEEL	TWA	10 mg/m3
	UK WEL	TWA	101 mg/m3 23 ppm
Ethanediol; ethylene glycol	ACGIH	Ceiling Aerosol.	100 mg/m3
	EU IOELV	TWA	52 mg/m3 20 ppm SKIN
	EU IOELV	STEL	104 mg/m3 40 ppm SKIN
	UK WEL	TWA	10 mg/m3 SKIN
		Particulate.	
	UK WEL	TWA Vapor.	52 mg/m3 20 ppm SKIN
	UK WEL	STEL Vapor.	104 mg/m3 40 ppm SKIN
	Ireland OELV	TWA Vapor.	52 mg/m3 20 ppm SKIN
		Indicative OELV	
	Ireland OELV	TWA	10 mg/m3 SKIN
		Particulate.	Indicative OELV
	Ireland OELV	STEL Vapor.	104 mg/m3 40 ppm SKIN
		Indicative OELV	
Polyethylene glycol	AIHA WEEL	TWA	10 mg/m3
		Particulate.	

A “skin” notation following the inhalation exposure guideline refers to the potential for dermal absorption of the material including mucous membranes and the eyes either by contact with vapors or by direct skin contact.

It is intended to alert the reader that inhalation may not be the only route of exposure and that measures to minimize dermal exposures should be considered.

8.2 Exposure controls

Personal Protection

Eye/Face Protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

Skin Protection: When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber (“latex”). Neoprene. Nitrile/butadiene rubber (“nitrile” or “NBR”). Polyethylene. Ethyl vinyl alcohol laminate (“EVAL”). Polyvinyl alcohol (“PVA”). Polyvinyl chloride (“PVC” or “vinyl”). When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Section 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties**Appearance**

Physical State	Liquid.
Color	Colorless
Odor	Mild
Odor Threshold	No test data available
pH	4.5 - 7.5 <i>ASTM E70</i> (5% aqueous solution)
Melting Point	Not applicable to liquids
Freezing Point	-65 °C <i>ASTM D1177</i> Sets to glass
Boiling Point (760 mmHg)	> 200 °C <i>Calculated</i> Decomposes.
Flash Point - Closed Cup	185 °C <i>ASTM D93</i>
Flash Point - Open Cup	191 °C <i>ASTM D92</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not applicable to liquids
Flammable Limits In Air	Lower: No test data available Upper: No test data available
Vapor Pressure	< 0.01 mmHg @ 20 °C <i>ASTM E1719</i>
Vapor Density (air = 1)	>1 <i>Calculated</i>
Specific Gravity (H2O = 1)	1.126 20 °C/20 °C <i>Calculated</i>
Solubility in water (by weight)	100 % @ 20 °C <i>Measured</i>
Partition coefficient, n-octanol/water (log Pow)	No data available for this product.
Autoignition Temperature	No test data available
Decomposition Temperature	No test data available
Kinematic Viscosity	42 - 47 cSt @ 25 °C <i>ASTM D445</i>
Explosive properties	no data available
Oxidizing properties	no data available

9.2 Other information

Molecular Weight	190 - 210 g/mol <i>Calculated</i>
-------------------------	-----------------------------------

Section 10. Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Thermally stable at typical use temperatures.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

10.5 Incompatible Materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

10.6 Hazardous decomposition products

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers. Carbon dioxide. Carboxylic acids. Polymer fragments.

Section 11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity

Ingestion

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

LD50, rat > 10,000 mg/kg

Aspiration hazard

Based on physical properties, not likely to be an aspiration hazard.

Dermal

Prolonged skin contact is unlikely to result in absorption of harmful amounts. Prolonged/repeated exposure to damaged skin (as in burn patients) may result in absorption of toxic amounts.

LD50, rabbit > 20,000 mg/kg

Inhalation

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. No adverse effects are anticipated from single exposure to mist. For respiratory irritation and narcotic effects: No relevant data found.

No deaths occurred at this concentration. LC50, 6 h, Aerosol, rat > 2.5 mg/l

Eye damage/eye irritation

May cause slight temporary eye irritation. Corneal injury is unlikely.

Skin corrosion/irritation

Prolonged contact is essentially nonirritating to skin.

Sensitization

Skin

Did not cause allergic skin reactions when tested in guinea pigs. Did not cause allergic skin reactions when tested in humans.

Respiratory

No relevant data found.

Repeated Dose Toxicity

Recent findings of kidney failure and death in burn patients, as well as some studies using animal burn models, suggest that polyethylene glycol may have been a factor. The use of topical applications containing this material may not be appropriate in severely burned patients or individuals with impaired renal function. Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Chronic Toxicity and Carcinogenicity

Did not cause cancer in laboratory animals.

Developmental Toxicity

Did not cause birth defects in laboratory animals.

Reproductive Toxicity

No relevant data found.

Genetic Toxicology

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Section 12. Ecological Information

12.1 Toxicity

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Fish Acute & Prolonged Toxicity

LC50, Pimephales promelas (fathead minnow), static test, 96 h: > 10,000 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, Daphnia magna (Water flea), 48 h: > 10,000 mg/l

12.2 Persistence and Degradability

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method	10 Day Window
85 %	28 d	OECD 301F Test	pass

12.3 Bioaccumulative potential

Bioaccumulation: No bioconcentration is expected because of the relatively high water solubility.

12.4 Mobility in soil

Mobility in soil: No data available.

12.5 Results of PBT and vPvB assessment

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

12.6 Other adverse effects

This substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Any disposal practice must be in compliance with all local and national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water.

Section 14. Transport Information

ROAD & RAIL

NOT REGULATED

OCEAN

NOT REGULATED

AIR

NOT REGULATED

INLAND WATERWAYS

NOT REGULATED

Section 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Inventory of Existing Commercial Chemical Substances (EINECS)

This product is a polymer according to the definition in Directive 92/32/EEC (7th Amendment to Directive 67/548/EEC) and all of its starting materials and intentional additives are listed in the European Inventory of Existing Commercial Chemical Substances (EINECS) or in compliance with European (EU) chemical inventory requirements.

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

15.2 Chemical Safety Assessment

Not applicable.

Section 16. Other Information

Hazard statement in the composition section

H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.

Risk-phrases in the Composition section

R22	Harmful if swallowed.
-----	-----------------------

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure. Additional information on this and other products may be obtained by visiting our web page.

Revision

Identification Number: 74379 / A279 / Issue Date 15.04.2013 / Version: 6.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

DOW CHEMICAL COMPANY LIMITED *urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.*

COMPANY INFORMATION DISTRIBUTOR		
name	BRENNTAG N.V.	BRENNTAG Nederland B.V.
address	Nijverheidslaan 38 8540 Deerlijk	Donker Duyvisweg 44 3316 BM Dordrecht
country	Belgium	The Netherlands
phone number	+32 (0)56 77 69 44	+31 (0)78 65 44 944
fax number	+32 (0)56 77 57 11	+31 (0)78 65 44 919
website	www.brenntag.be	www.brenntag.nl
e-mail	info@brenntag.be	info@brenntag.nl
activities	Distribution and export of chemicals and raw materials	
VAT number	BE0405317567	NL001375945B01
recall procedure available	Yes	
emergency number (24/365)	+32 (0)56 77 69 44	+31 (0)78 6544 944
QUALITY SYSTEMS		
ISO 9001	Yes	Yes
ISO 14001	Yes	Yes
ISO 22000	Yes	Yes
FSSC 22000	Yes	Yes
GMP+ -feed	Yes	Yes
OHSAS18001	-	Yes
ESAD	Yes	Yes
other	-	AEO