

 <p>DOW BENELUX B.V.</p> <p>75302445 22284000 NL02067481</p>	<p>BRENNTAG NEDERLAND BV JUPITERWEG 3 4761 RW MOERDIJK</p> <p>Ship From: HOEK Netherlands</p>																																																										
<p align="center">Certificate of Analysis</p> <p>Product Number 00000217616 Product Name CARBOWAX™ PEG 400E Delivery No. 813960958 / 000030 Order Number 108708524 Date Shipped 2018-09-13 (YYYY-MM-DD) Shipment No. 32983006</p>	<p align="center">Customer Information</p> <p>Customer Name BRENNTAG NEDERLAND BV Customer PO number 75302445 Customer Product Code 22284000 Container ID OD21DV Vehicle# 51BKP9 Specification Number 000000073285</p>																																																										
<p>Batch Number F359I93L02 Manufacturing Date 2018-09-03 (YYYY-MM-DD)</p>																																																											
<table border="1"> <thead> <tr> <th>Test</th> <th>Unit</th> <th>Lower Limit</th> <th>Upper Limit</th> <th>Value</th> <th>Method</th> </tr> </thead> </table>						Test	Unit	Lower Limit	Upper Limit	Value	Method																																																
Test	Unit	Lower Limit	Upper Limit	Value	Method																																																						
<table border="1"> <tbody> <tr> <td>Acidity as acetic acid</td> <td>WT%</td> <td>-</td> <td>0,0500</td> <td>0,0110</td> <td>DOWM 101370</td> </tr> <tr> <td>Color, Pt-Co</td> <td></td> <td>-</td> <td>40</td> <td>8</td> <td>ASTM D1209</td> </tr> <tr> <td>MEG + DEG</td> <td>WT%</td> <td>-</td> <td>0,20</td> <td>0,06</td> <td>DOWM 101368</td> </tr> <tr> <td>Avg. Molecular Wt.</td> <td></td> <td>380</td> <td>420</td> <td>393</td> <td>ASTM D4274</td> </tr> <tr> <td>pH 5% aqueous solution</td> <td></td> <td>4,5</td> <td>7,5</td> <td>5,7</td> <td>DOWM 101371</td> </tr> <tr> <td>Residue on Ignition</td> <td>WT%</td> <td>-</td> <td>0,0500</td> <td>0,0400</td> <td>ASTM D1119</td> </tr> <tr> <td>Viscosity @ 25degC</td> <td>cSt</td> <td>76</td> <td>86</td> <td>81</td> <td>ASTM D445</td> </tr> <tr> <td>Water Content</td> <td>WT%</td> <td>-</td> <td>0,500</td> <td>0,078</td> <td>ASTM E203</td> </tr> <tr> <td>Water Solubility @ 25DEGC ESSENTIALLY COMPLETE</td> <td>-</td> <td>-</td> <td>-</td> <td>Pass</td> <td>Visual</td> </tr> </tbody> </table>						Acidity as acetic acid	WT%	-	0,0500	0,0110	DOWM 101370	Color, Pt-Co		-	40	8	ASTM D1209	MEG + DEG	WT%	-	0,20	0,06	DOWM 101368	Avg. Molecular Wt.		380	420	393	ASTM D4274	pH 5% aqueous solution		4,5	7,5	5,7	DOWM 101371	Residue on Ignition	WT%	-	0,0500	0,0400	ASTM D1119	Viscosity @ 25degC	cSt	76	86	81	ASTM D445	Water Content	WT%	-	0,500	0,078	ASTM E203	Water Solubility @ 25DEGC ESSENTIALLY COMPLETE	-	-	-	Pass	Visual
Acidity as acetic acid	WT%	-	0,0500	0,0110	DOWM 101370																																																						
Color, Pt-Co		-	40	8	ASTM D1209																																																						
MEG + DEG	WT%	-	0,20	0,06	DOWM 101368																																																						
Avg. Molecular Wt.		380	420	393	ASTM D4274																																																						
pH 5% aqueous solution		4,5	7,5	5,7	DOWM 101371																																																						
Residue on Ignition	WT%	-	0,0500	0,0400	ASTM D1119																																																						
Viscosity @ 25degC	cSt	76	86	81	ASTM D445																																																						
Water Content	WT%	-	0,500	0,078	ASTM E203																																																						
Water Solubility @ 25DEGC ESSENTIALLY COMPLETE	-	-	-	Pass	Visual																																																						
<p>Quality Coordinator</p> <p>For inquiries please contact Customer Service or local sales</p> <p>® ™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow</p>																																																											