

Safety Data Sheet DOW CHEMICAL COMPANY LIMITED

Product Name: CARBOWAX™ PEG 400E

Revision Date: 15.04.2013 Print Date: 05 Jun 2014

DOW CHEMICAL COMPANY LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

Section 1. Identification of the substance/preparation and of the company/undertaking

1.1 Product identifiers Product Name CARBOWAX™ PEG 400E

Chemical Name: Polyethylene glycol CAS-No. 25322-68-3

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses

A partial list of examples include pharmaceutical products, personal care products, automotive products, household products, packaging products, petroleum chemicals, plastics, inks, coatings, adhesives, chemical intermediates, rubber processing, lubricants, metalworking fluids, mold release agents, ceramics, and wood treating. CAUTION! For food, feed, drug or cosmetic applications, use CARBOWAX[™] SENTRY[™] brands, NF (National Formulary), FCC (Food Chemical Codex) Grade. Only SENTRY brand products are tested to meet NF and FCC standards for these applications.

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION

DOW CHEMICAL COMPANY LIMITED DIAMOND HOUSE, LOTUS PARK, KINGSBURY CRESCENT, STAINES England TW18 3AG UNITED KINGDOM

Customer Information Number:

0203 139 4000 SDSQuestion@dow.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: Local Emergency Contact:

0031 115 694 982 00 31 115 69 4982

Hazards Identification Section 2.

2.1 Classification of the substance or mixture Classification - REGULATION (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria. Classification according to EU Directives 67/548/EEC or 1999/45/EC This product is not classified as dangerous according to EC criteria.

Additional Information

Safety data sheet available for professional users on request.

2.2 Label elements

Labelling - REGULATION (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria.

2.3 Other Hazards

No information available.

Composition/information on ingredients Section 3.

3.1 Substance

This product is a substa CAS-No. / EC-No. / Index	nce. REACH No.	Amount	Component	Classification: REGULATION (EC) No 1272/2008	
CAS-No. 25322-68-3 EC-No. Polymer	_	100.0 %	Polyethylene glycol#	Not classified	

CAS-No. / EC-No. / Index	Amount	Component	Classification: 67/548/EEC
CAS-No. 25322-68-3 EC-No. Polymer	100.0 %	Polyethylene glycol#	Not classified.

Substance(s) with an Occupational Exposure Limit. For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4. **First-aid measures**

4.1 Description of first aid measures

General advice: If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin Contact: Wash skin with plenty of water.

Eye Contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

4.2 Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), no additional symptoms and effects are anticipated.

4.3 Indication of immediate medical attention and special treatment needed

Absorption may be promoted by damaged skin. J Pharm Sci. 1985 Oct;74(10):1062-6; Burns Incl Therm Inj 1982 Sep;9(1):49-52. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5. Fire Fighting Measures

5.1 Extinguishing Media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Extinguishing Media to Avoid: Do not use direct water stream. May spread fire.

5.2 Special hazards arising from the substance or mixture

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. **5.3 Advice for firefighters**

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

6.2 Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

6.3 Methods and materials for containment and cleaning up: Contain spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

Section 7. Handling and Storage

7.1 Precautions for safe handling

Handling

General Handling: See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Other Precautions: Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

7.2 Conditions for safe storage, including any incompatibilities Storage

Store in original container. Use product promptly after opening. Avoid prolonged exposure to heat and air. Store in the following material(s): Stainless steel. Polypropylene. Polyethylene-lined container. Teflon. Glass-lined container. Plasite 3066 lined container. Plasite 3070 lined container. 316 stainless steel.

7.3 Specific end uses

See the technical data sheet on this product for further information.

Section 8. Exposure Controls / Personal Protection

8.1 Control parameters Exposure Limits			
Component	List	Туре	Value
Polyethylene glycol	AIHA WEEL	TWA Particulate.	10 mg/m3

8.2 Exposure controls

Personal Protection

Eye/Face Protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

Skin Protection: When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit

requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Section 9. Physical and Chemical Properties

9.1 Information on basic phys	ical and chemical properties
Appearance	
Physical State	Liquid.
Color	Colorless
Odor	Mild
Odor Threshold	No test data available
рН	4.5 - 7.5 ASTM E70 (5% aqueous solution)
Melting Point	Not applicable to liquids
Freezing Point	4 - 8 °C ASTM D1171
Boiling Point (760 mmHg)	> 200 °C Calculated Decomposes.
Flash Point - Closed Cup	227 °C ASTM D93
Flash Point - Open Cup	263 °C <i>ASTM D92</i>
Evaporation Rate (Butyl	No test data available
Acetate = 1)	
Flammability (solid, gas)	Not applicable to liquids
Flammable Limits In Air	Lower: No test data available
	Upper: No test data available
Vapor Pressure	< 0.01 mmHg @ 20 °C ASTM E1719
Vapor Density (air = 1)	>1 Calculated
Specific Gravity (H2O = 1)	1.127 20 °C/20 °C Calculated
Solubility in water (by	100 % @ 20 °C Measured
weight)	
Partition coefficient. n-	No data available for this product.
octanol/water (log Pow)	l l
Autoignition Temperature	No test data available
Decomposition	No test data available
Temperature	
Kinematic Viscosity	76 - 86 cSt @ 25 °C ASTM D445
Explosive properties	no data available
Oxidizing properties	no data available
51 1	
9.2 Other information	
Molecular Weight	380 - 420 g/mol Calculated

Section 10. Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use. **10.2 Chemical stability** Thermally stable at typical use temperatures.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

10.5 Incompatible Materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers. **10.6 Hazardous decomposition products**

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers. Carbon dioxide. Carboxylic acids. Polymer fragments.

Section 11. Toxicological Information

11.1 Information on toxicological effects Acute Toxicity

Ingestion

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. LD50, Rat > 10.000 mg/kg

Aspiration hazard

Based on physical properties, not likely to be an aspiration hazard.

Dermal

Prolonged skin contact is unlikely to result in absorption of harmful amounts. Prolonged/repeated exposure to damaged skin (as in burn patients) may result in absorption of toxic amounts.

LD50, Rabbit > 20,000 mg/kg

Inhalation

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. For respiratory irritation and narcotic effects: No relevant data found.

Typical for this family of materials. No deaths occurred at this concentration. LC50, 6 h, Aerosol, Rat > 2.5 mg/l

Eye damage/eye irritation

May cause slight temporary eye irritation. Corneal injury is unlikely.

Skin corrosion/irritation

Prolonged contact is essentially nonirritating to skin.

Sensitization

Skin

Did not cause allergic skin reactions when tested in humans.

Respiratory

No relevant data found.

Repeated Dose Toxicity

Recent findings of kidney failure and death in burn patients, as well as some studies using animal burn models, suggest that polyethylene glycol may have been a factor. The use of topical applications containing this material may not be appropriate in severely burned patients or individuals with impaired renal function. Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Chronic Toxicity and Carcinogenicity

Did not cause cancer in laboratory animals.

Developmental Toxicity

For similar material(s): Did not cause birth defects in laboratory animals.

Reproductive Toxicity

For similar material(s): In animal studies, did not interfere with reproduction.

Genetic Toxicology

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Section 12. Ecological Information

12.1 Toxicity

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Fish Acute & Prolonged Toxicity

LC50, fathead minnow (Pimephales promelas), static, 96 h: 87,209 mg/l Aquatic Invertebrate Acute Toxicity LC50, water flea Daphnia magna, static, 48 h: 53,484 mg/l

12.2 Persistence and Degradability

Material is expected to be readily biodegradable.

12.3 Bioaccumulative potential

Bioaccumulation: No bioconcentration is expected because of the relatively high water solubility.

12.4 Mobility in soil

Mobility in soil: No data available.

12.5 Results of PBT and vPvB assessment

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

12.6 Other adverse effects

This substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Any disposal practice must be in compliance with all local and national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water.

Section 14. Transport Information

ROAD & RAIL

NOT REGULATED

OCEAN

NOT REGULATED

AIR NOT REGULATED

INLAND WATERWAYS

NOT REGULATED

Section 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

European Inventory of Existing Commercial Chemical Substances (EINECS)

This product is a polymer according to the definition in Directive 92/32/EEC (7th Amendment to Directive 67/548/EEC) and all of its starting materials and intentional additives are listed in the European Inventory of Existing Commercial Chemical Substances (EINECS) or in compliance with European (EU) chemical inventory requirements.

15.2 Chemical Safety Assessment

Not applicable.

Section 16. Other Information

Hazard statement in the composition section

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure. Additional information on this and other products may be obtained by visiting our web page.

Revision

Identification Number: 74381 / A279 / Issue Date 15.04.2013 / Version: 4.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

DOW CHEMICAL COMPANY LIMITED urges each customer or recipient of this (*M*)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (*M*)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (*M*)SDSs, we are not and cannot be responsible for (*M*)SDS obtained from any source other than ourselves. If you have obtained an (*M*)SDS from another source or if you are not sure that the (*M*)SDS you have is current, please contact us for the most current version.



COMPANY INFORMATION DISTRIBUTOR

name	BRENNTAG N.V.	BRENNTAG Nederland B.V.
address	Nijverheidslaan 38 8540 Deerlijk	Donker Duyvisweg 44 3316 BM Dordrecht
country	Belgium	The Netherlands
phone number	+32 (0)56 77 69 44	+31 (0)78 65 44 944
fax number	+32 (0)56 77 57 11	+31 (0)78 65 44 919
website	www.brenntag.be	www.brenntag.nl
e-mail	info@brenntag.be	info@brenntag.nl
activities	Distribution and export of chemicals and raw materials	
VAT number	BE0405317567	NL001375945B01
recall procedure available	Yes	
emergency number (24/365)	+32 (0)56 77 69 44	+31 (0)78 6544 944
QUALITY SYSTEMS		
ISO 9001	Yes	Yes
ISO 14001	Yes	Yes
ISO 22000	Yes	Yes
FSSC 22000	Yes	Yes
GMP+ -feed	Yes	Yes
OHSAS18001	-	Yes
ESAD	Yes	Yes
other	-	AEO

