

07932 Dammar Varnish Matte

1. Identification of the Substance/Mixture and of the Company/Undertaking

1.1. Product Identifier

Product Name: Dammar Varnish Matte

Article No.: O7932

UFI: --

1.2. Relevant identified Uses of the Substance or Mixture and Uses advised against

Identified uses:
No information available

Uses advised against:

1.3. Details of the Supplier of the Safety Data Sheet (Producer/Importer)

Company: Interlabshop BV

Address: Lage Brink 23, 7317BD Apeldoorn The Netherlands

Tel./Fax.: +31(0)55-5215016

Internet: www.labshop.nl

EMail: labshop@labshop.nl

Importer: --

1.4. Emergency No.

Emergency No.: +31(0)55-5215016 (Mon-Fri 8:30 - 17:30)

1.4.2 Poison Center:

2. Hazards Identification

2.1. Classification of the Substance or Mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

Flammable liquids, hazard category 3
Acute toxicity (oral), hazard category 4
Acute toxicity (dermal), hazard category 4
Skin irritation, hazard category 2
Skin sensitization, hazard category 1
Eye irritation, hazard category 2
Chronic aquatic toxicity, hazard category 2
Acute toxicity (inhalation), hazard category 4

H226 Flammable liquid and vapour.

Cat.: 3

H302+H312 Harmful if swallowed or in contact with skin.

Cat.: 4

H315 Causes skin irritation.

Cat.: 2

H317 May cause an allergic skin reaction.

Cat.: 1

H319 Causes serious eye irritation.

Cat.: 2

H332 Harmful if inhaled.

Cat.: 4

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)

07932 Dammar Varnish Matte

Page 2

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

H411 Toxic to aquatic life with long lasting effects.
Cat.: 2

Possible Environmental Effects:

See Section 12.

2.2. Label Elements

*Classification according to Regulation
(EC) No. 1272/2008 (CLP/GHS)*

Hazard designation:



GHS02-1



GHS07



GHS09

Signal word:

Warning

Hazard designation:

H226	Flammable liquid and vapour.
H302+H312	Harmful if swallowed or in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Safety designation:

P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P273	Avoid release to the environment.
P301+P310	If swallowed: Immediately call a poison center or physician.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P331	Do not induce vomiting.

Hazardous components for labelling:

Turpentine, oil

2.3. Other Hazards

3. Composition/Information on Ingredients

3.1. Substance

3.2. Mixture

Chemical Characterization:

Mixture of different terpenes with dammar (1:2) and bleached beeswax as dulling agent.

next page: 3

07932 Dammar Varnish Matte

Page 3

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

*Information on Components / Hazardous**Ingredients:*

Turpentine oil (H226-302-304-312-315-317-319-332-411); REACH Reg. No. 01-2119553060-53-0007	> 50 %	CAS-Nr: (8006-64-2) EINECS-Nr: 932-349-8 (232-350-7) EC-Nr: 650-002-00-6
---	--------	--

Additional information:

4. First Aid Measures**4.1. Description of the First Aid Measures***General information:*

*Remove contaminated clothes immediately.
Take person away from hazardous area.
Intoxication symptoms may occur after several hours, therefore a 48 hour medical observation is necessary.
Consult physician.*

After inhalation:

Supply fresh air. If required give artificial respiration. In case of complaints or unconsciousness consult a physician. In case of unconsciousness place patient stable in side position for transportation.

After skin contact:

Wash off with plenty of water and soap. Consult a physician if irritation persists.

After eye contact:

Rinse open eyes with plenty of water. In case of discomfort seek medical help.

After ingestion:

*Rinse mouth with plenty of water and consult physician.
Do not induce vomiting.*

4.2. Most important Symptoms and Effects, both Acute and Delayed*Symptoms:*

No further information available.

Effects:

No further information available.

4.3. Indication of any Immediate Medical Attention and special Treatment needed*Treatment:*

Treat symptomatically.

5. Fire-Fighting Measures**5.1. Extinguishing Media***Suitable extinguishing media:*

Water mist, extinguishing powder, foam, carbon dioxide.

Unsuitable extinguishing media:

Water with full jet.

next page: 4

07932 Dammar Varnish Matte

Page 4

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

5.2. Special Hazards arising from the Substance or Mixture*Special hazards:*

*In case of fire: formation of carbon oxides.
Flammable.
Fumes can form an explosive mixture with air.*

5.3. Advice for Firefighters*Protective equipment:*

*Wear self-contained respiratory protective device.
Wear suitable protective clothing.*

Further information:

*Cool closed containers exposed to fire with water mist.
Collect contaminated extinguishing water and debris separately;
avoid contamination of sewage system.*

6. Accidental Release Measures**6.1. Personal Precautions, Protective Equipment and Emergency Procedures***Personal precautions:*

*Wear protective clothing.
Provide adequate ventilation. Keep away from sources of ignition.
Avoid contact with eyes and skin.
Do not inhale aerosol/fumes/vapors.*

6.2. Environmental Precautions*Environmental precautions:*

*Prevent contamination of soils, drains and surface water.
Contact local authorities if product pollutes soil or vegetation.*

6.3. Methods and Material for Containment and Cleaning Up*Methods and material:*

*Contain with non-flammable absorbent material (e.g. sand, diatomaceous earth, vermiculite) and dispose accordingly.
Dispose of contaminated material as waste according to section 13.*

6.4. Reference to other Sections

Protective clothing, see Section 8.

7. Handling and Storage**7.1. Precautions for Safe Handling***Instructions on safe handling:*

*The usual precautionary measures are to be adhered to when handling chemicals.
Avoid contact with eyes and skin.
Provide good ventilation and/or exhaust at the workplace. Ensure adequate ventilation. Handle and open container with care.*

Hygienic measures:

*Take off contaminated clothing immediately.
Keep away from foodstuffs and drinks. Do not eat, drink or smoke during work. Wash hands before breaks and at the end of work.*

next page: 5

O7932 Dammar Varnish Matte

Page 5

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

A nearby eyewash facility should be available for emergencies.

7.2. Conditions for Safe Storage, including any Incompatibilities*Storage conditions:*

Store the product in the original tightly sealed containers in a dry and cool place.

Protect against heat.

Requirements for storage areas and containers:

Store in a room with a solvent-proof floor.

Information on fire and explosion protection:

Keep away from sources of ignition - do not smoke. Take measures to prevent electrostatic discharge.

Do not store together with combustible and self-ignitable products.

Dust may form an explosive mixture with air.

Combustible liquid.

Vapors may form an explosive mixture with air. Vapor is heavier than air and spreads along the ground.

Storage class:

3; Flammable liquids (TRGS 510)

Further Information:

The product is slightly hazardous to water. Consider national regulations regarding handling and storage.

7.3. Specific End Use(s)*Further information:*

No information available.

8. Exposure Controls/Personal Protection**8.1. Parameters to be Controlled***Parameters to be controlled (DE):*

Turpentine oil (CAS 8006-64-2): TWA: 8.2 mg/m³, 2 ppm (long-term value); 16.4 mg/m³, 4 ppm (short-term value)

*Parameters to be controlled:**Derived No-Effect Level (DNEL):**Turpentine oil:*

161 µg/cm² (worker, skin contact, short-term exposure)

5.98 mg/m³ (worker, inhalation, long-term exposure)

81 µg/cm² (consumer, skin contact, short-term exposure)

0.31 mg/kg bw/d (consumer, swallowing, long-term exposure)

1.06 mg/m³ (consumer, inhalation, long-term exposure - local effects)

*Predicted No-Effect Concentration (PNEC):**Turpentine oil (CAS 8006-64-2):*

Fresh water: 8.8 µg/l

Sea water: 0.88 µg/l

next page: 6

O7932 Dammar Varnish Matte

Page 6

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

Fresh water sediment: 2.27 mg/kg dw
Sea water sediment: 0.227 mg/kg dw
Oral (secondary poisoning): 1.35 mg/kg (feed)
Sewage treatment system (STP): 6.6 mg/l
Soil: 0.45 mg/kg

*Additional Information:***8.2. Exposure Controls***Technical protective measures:*

Ensure adequate ventilation, especially in confined areas.
Facilities storing or utilizing this material should be equipped with an eyewash facility.

*Personal Protection**General protective measures:*

Remove contaminated clothing immediately.
Do not inhale gas/fumes/vapor/aerosol.
Keep away from foodstuffs and drinks. Do not eat, drink or smoke during work. Wash hands before breaks and at the end of work.

Respiratory protection:

Respiratory equipment required in case of insufficient ventilation, filter type A.

Hand protection:

Protective gloves
The manufacturer's directions for use should be observed because of the great diversity of types.

Protective glove material:

Nitrile rubber (> 480 min, 0.35 mm)

Eye protection:

Tightly fitting safety goggles (EN 166).

Body protection:

Protective clothing, chemical resistant.

Environmental precautions:

Prevent contamination of open water ways and sewage system.
Avoid contamination of ground water.
Contact local authorities if large spillages cannot be contained.

9. Physical and Chemical Properties**9.1. Information on Basic Physical and Chemical Properties**

Form: liquid
Color: colorless
Odor: like turpentine
Odor threshold: no information available
pH-Value: not applicable

next page: 7

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)

07932 Dammar Varnish Matte

Page 7

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

Melting temperature:

not available

Boiling temperature:

not available

Flash point:

23°C

Evaporation rate:

No information available.

Flammability (solid, gas):

not applicable

Upper explosion limit:

no information available

Lower explosion limit:

no information available

Vapor pressure:

not determined

Vapor density:

No information available.

Density:

not available

Solubility in water:

practically insoluble

*Coefficient of variation (n-
Octanol/Water):*

no information available

Auto-ignition temperature:

Decomposition temperature:

No data available.

Viscosity, dynamic:

not available

Explosive properties:

Product is not explosive; however, an explosive vapor/air mixture can be formed.

Oxidizing properties:

none

Bulk density:

not determined

9.2. Further Information

Solubility in solvents:

Viscosity, kinematic:

Burning class:

Solvent content:

07932 Dammar Varnish Matte

Page 8

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

Solid content:

Particle size:

Other information:

No further information.

10. Stability and Reactivity

10.1. Reactivity

No information available.

10.2. Chemical Stability

No decomposition if used according to specifications.

10.3. Possibility of Hazardous Reactions

Incompatible with strong oxidizing agents.

10.4. Conditions to Avoid

Conditions to avoid:

No information available.

Thermal decomposition:

No data available.

10.5. Incompatible Materials

Oxidizing agents.

10.6. Hazardous Decomposition Products

Carbon monoxide, carbon dioxide and hydrocarbons.

10.7. Further Information

11. Toxicological Information

11. 1. Information on Toxicological Effects

Acute Toxicity

LD50, oral:

Turpentine oil: 3956 mg/kg (rat)

LD50, dermal:

Turpentine oil: > 2000 mg/kg (rabbit)

LC50, inhalation:

Turpentine oil: 13.7 mg/l (4h, rat; OECD 403); 29 mg/l (2h, mouse; OECD 403)

Primary effects

Irritant effect on skin:

Turpentine oil: irritating (rabbit)

Irritant effect on eyes:

Turpentine oil: irritating (rabbit)

Inhalation:

No information available.

Ingestion:

No information available

Sensitization:

next page: 9

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)

07932 Dammar Varnish Matte

Page 9

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

Turpentine oil: May cause an allergic skin reaction.

Mutagenicity:

No relevant data found.

Reproductive toxicity:

No information available.

Carcinogenicity:

No relevant data found.

Teratogenicity:

No information available.

Specific target organ toxicity (STOT):

No relevant data found.

Additional toxicological information:

Turpentine oil:

Aspiration toxicity: may be fatal if swallowed and enters airways.

May cause an allergic skin reaction.

Harmful. Irritating.

Risk of skin absorption.

12. Ecological Information

12.1. Aquatic Toxicity

Fish toxicity:

No data available.

Daphnia toxicity:

Turpentine oil: EC50: 14.1 mg/l

Bacteria toxicity:

Turpentine oil: EC50: 736 mg/l (3h, aquatic microorganisms; OECD 209)

Algae toxicity:

No information available.

12.2. Persistency and Degradability

Turpentine oil: > 80 % (28d); Readily biodegradable (OECD 301E)

12.3. Bioaccumulation

Turpentine oil: An appreciable bioaccumulation potential is to be expected ($\log P(o/w) > 3$).

12.4. Mobility

No information available.

12.5. Results of PBT- und vPvP Assessment

This product is neither a PBT or vPvB substance nor does it contain a PBT or vPvB substance.

12.6. Other Adverse Effects

Water hazard class:

2 (German Regulation) (Assessment by list): hazardous.

Behaviour in sewage systems:

next page: 10

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)

O7932 Dammar Varnish Matte

Page 10

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

Further ecological effects:

*May cause long-term adverse effects in the aquatic environment.
Prevent product from entering surface water and drains.
The data is based on the solvent contained.*

AOX Value:

13. Disposal Considerations

13.1. Waste Treatment Methods

Product:

*Must be treated as toxic waste according to local laws and regulations.
Must not be disposed together with household garbage.*

European Waste Code (EWC):

Uncleaned packaging:

Drain container thoroughly. After draining, vent in a safe place away from sparks and fire.

Waste Code No.:

14. Transport Information

14.1. UN Number

ADR, IMDG, IATA 1263

14.2. UN Proper Shipping Name

ADR/RID: FARBE

IMDG/IATA: PAINT

14.3. Transport Hazard Classes

ADR Class: 3

Hazard no.: 3

Classification code: F1

Tunnel restriction code: D/E

IMDG Class (sea): 3

Hazard no.: 3

EmS No.: F-E, S-E

IATA Class: 3

Hazard no.: 3

14.4. Packaging Group

ADR/RID: III

IMDG: III

IATA: III

14.5. Environmental Hazards

*Labelling according 5.2.1.8 ADR/RID: fish and tree
Labelling according 5.2.1.6.3 IMDG: fish and tree*

next page: 11

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)

07932 Dammar Varnish Matte

Page 11

Revised edition: 03.06.2022

Version: 1

Printed: 03.06.2022

Classification as environmentally hazardous according 2.9.3

IMDG: yes

Labelled with "P" according 2.10 IMDG: yes

14. 6. Special Precautions for User

not applicable

14. 7. Transportation in Bulk according to Annex II of MARPOL 73/78 and IBC-Code

IMDG: not applicable

14. 8. Further Information

15. Regulatory Information

15. 1. Safety, Health and Environmental Regulations/Legislation specific for the Substance or Mixture

Water hazard class:

2, hazardous for water (German Regulation)

Local regulations on chemical accidents:

Employment restrictions:

The employment restrictions for expectant and nursing mothers, and for young workers are to be observed.

Restriction and prohibition of application:

Technical instructions on air quality:

15. 2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

15. 3. Further Information

16. Other Information

This product should be stored, handled and used in accordance with good hygiene practices and in conformity with any legal regulations. This information contained herein is based on the present state of knowledge and is intended to describe our product from the point of view of safety requirements. It should be therefore not be construed as guaranteeing specific properties.